



CLIENT PROJECT REPORT CPR1490

Assessment of Radlock Highway Systems Composite Plate with Locking Mechanism

R W Jordan and C Sadat-Shafae

Prepared for: Radlock Highways Systems LLP
Project Ref: 020528

Quality approved:

Chris Sadat Shafae
(Project Manager)



Ian Carswell
(Technical Referee)



Disclaimer

This report has been produced by the Transport Research Laboratory under a contract with Radlock Highways Systems LLP. Any views expressed in this report are not necessarily those of Radlock Highways Systems LLP.

The information contained herein is the property of TRL Limited and does not necessarily reflect the views or policies of the customer for whom this report was prepared. Whilst every effort has been made to ensure that the matter presented in this report is relevant, accurate and up-to-date, TRL Limited cannot accept any liability for any error or omission, or reliance on part or all of the content in another context.

Contents amendment record

This report has been amended and issued as follows:

Version	Date	Description	Editor	Technical Referee
V1.0	21/12/12	Report issued	IC	IC

Contents

Executive summary	ii
1 Introduction	1
2 Tests on surface mounted final design plates in the Pavement Test Facility	3
2.1 The PTF	3
2.2 Test setup	3
2.3 Development of final design plates	4
2.4 Test conditions	5
2.5 Test findings	5
2.6 Comments on mode of failure	8
2.7 Comparison of test conditions and wheel loading on roads	8
2.7.1 Equivalent number of standard axles	8
2.7.2 Wheels travelling along the plates	9
2.7.3 Wheels travelling across the plates	12
2.7.4 Typical usage at linear and transverse trenches	12
3 Conclusions	13
Acknowledgements	14
References	14

Executive summary

This report describes the testing of a composite plate with integral locking mechanism supplied by Radlock Highways Systems under repeated trafficking to assess its suitability for use on the road network to cover trenches up to 700mm wide during utility and highway works.

The plates can be handled and positioned fairly quickly by two reasonably fit people. The locking mechanism can be attached quickly when the plates are nearly in position over the trench, and can be engaged with the sides of the trench quickly when the plate has been manoeuvred into its final position. .

The plates failed after a total of over 65,000 passes, comprising 50,000 passes of a super single wheel at 4 tonnes and a further 15,541 passes of a super single wheel at 5.5 tonnes along a linear run placed over a trench of width 700 mm. This testing regime was very severe with a single wheel running along the centreline of the trench at every pass in both directions.

Taking all factors into account, it is concluded that the total passes in the tests represented typical use over a minimum period of at least 3 years on Type 1 roads, and it is anticipated that much of their use will also be on Type 3 and 4 roads thus extending that period.

The Radlock Composite Road Plates complete with the Radlock Series 15 Locking Mechanism are recommended for use on site.




Figure 1.1 – A run of prototype plates




Figure 1.2 – Underside of a final design plate

3 Conclusions

Installation

- The plates can be handled and positioned by two reasonably fit people.
- Whereas the plates can be handled with the locking mechanisms in position, it is easier to store and position the plates if the locking mechanisms are attached to the plates when they are over the trench.
- The locking mechanism can be fitted to a plate in less than a minute. The locking mechanism can be engaged with the sides of the trench in a similar time. Therefore, an installation of surface mounted plates can be completed in a short time.

Performance

- The final design plates failed after over 65,000 passes, comprising 50,000 passes of a super single wheel at 4 tonnes and a further 15,541 passes of a super single wheel at 5.5 tonnes along a linear trench of width 700 mm.
- The test conditions were severe. The linear trafficking loaded the edge of the plates on every pass. The trench width was 700 mm and wider than most trenches at which the plates would be used on roads. Some, probably more, installations will be at transverse trenches rather than at linear trenches. The loading on transverse trenches will be less onerous than that at linear trenches.
- The production version of the final design plates that will be used on roads will be stronger than the final design plates that were tested as the load transfer links will be an integral part of the reinforcement mesh. Taking all factors into account, it is concluded that the total passes in the tests represented typical use over a period of at least 3 years on Type 1 roads.
- The Radlock Series 15 locking mechanisms were considered to be robust and showed no signs of failure during the testing.
- The Radlock Composite Road Plates with Radlock Series 15 locking mechanism as the fixing method are recommended for use on site and the development of case studies on their use is also recommended.

Acknowledgements

The work described in this report was carried out in the Infrastructure Division of the Transport Research Laboratory. The authors are grateful to Ian Carswell who carried out the technical review and auditing of this report.; and to James Weeks, Kevin Green, Bobby Meitei, Phil Hannah and Simon Brown for their assistance with these trials.

References

R W Jordan, N Anderson, C Sadat-Shafae and B Meitei (2013 - to be published). Reducing congestion on the road network: Part 1, Use of road plates .
TRL Published Project Report. Crowthorne: Transport Research Laboratory.